



centro ricerche-sviluppo e laboratori prove
 settori legno-arredo, ambiente e alimenti

CATAS S.p.A.
 Iscr. Reg. Imprese Udine
 nr. iscr. C.F. 01818850305
 Reg. Impr. UD 20663
 P. IVA : 01818850305
 C.Soc. € 1.003.650,00 i.v.

Sede: Via Antica, 24/3
 33048 S. Giovanni al Nat. UD
 Tel. 0432.747211 r.a.
 Fax 0432.747250
<http://www.catas.com>
 e-mail: lab@catas.com

Filiale:
 Via Braille, 5
 20851 Lissone MB
 Tel. 039.464567
 Fax 039.464565
 e-mail: lissone@catas.com



TEST REPORT

141022 / 3

Date received: 07-05-12
 Date of test: 15-05-12
 Date of issue: 15-05-12
 Sample name: "OFFICE"

MANIFATTURA LANE CHIOCCARELLO S.R.L.
 VIA BRUNO BRANDELLERO, 9
 36036 TORREBELVICINO (VI)
 ITALIA

Ignitability of upholstered seating BS 5852:2006 (Clause 11 Crib 5)

This test is referred to in BS 7176:2007 (Medium hazard).

Description of tested materials as declared by the client

Cover material

Fabric OFFICE produced by Manifattura Lane Chioccarello S.r.l. Company, composition 100 % polyester FR, mass per unit area 430 g/m². The cover has not been treated with a fire-retardant chemical, the exposed surface of the cover was tested.

Filling material

Polyurethane foam T 40/RC 5E produced by Olmo Giuseppe S.p.a. Company, density 40 kg/m³.

Pre-treatment

The cover has not been subjected to the water soaking and drying procedure (Annex E) prior to being conditioned has set out in Clause 10.1.2.

Conditioning

At least 96 hours at 23 ± 2 °C temperature and 50 ± 5 % relative humidity.

Requirements

BS 5852:2006, Clause 11.

Test results

Application	Duration of flames from start of test	Duration of smouldering after 60 min.	Other requirements of Clause 11	Comments	Result
N. 1	-	-	-	-	-
N. 2	-	-	-	-	-

The uncertainties of measurement extended to a 95 % level of confidence (coverage factor k=2) are ± 0,2 seconds and ± 0,6 mm.

The above test results relate only to the ignitability of the combination of upholstery composites (Clause 11 of BS 5852:2006) under the particular conditions of test stated; they are not intended as a means of assessing the full potential fire hazard of the materials or products in use.

This document is validated by digital signature and time stamping in accordance with the Italian laws and the European Directives which regulate the electronic signature systems.

Managing Director
Dr. Andrea Giavotti

The sample name and, when relevant, its description, are given by the orderer, and CATAS does not assume responsibility on this matter. This test report relates to the sample submitted for the test and no others. Additions, deletions or alterations are not permitted. This test report must always be reproduced in its entirety. Unless otherwise stated, sampling has been carried out by the orderer.

pag. 1/1